

# COOLIUS A10

**A/C SERVICE UNIT**

**STRONGER PRICE-  
PERFORMANCE RATIO**

**MOBILE & FLEXIBLE**

**NO UNWANTED ACCESS**

Personalised access  
using a 4-digit password

Art. No. W050101008



**PRE-SALE!  
ORDER NOW**

# A/C SERVICE UNIT



## EFFICIENT IN MOBILE USE

- Innovative vehicle design with transport guard
- Highest level of impact reduction
- Operation possible with voltage transformer

## PROFESSIONAL DOCUMENTATION

- Exporting of data to Excel via USB interface
- Documentation of individual services
- Evaluation of total refrigerant consumption

## LONG SERVICE INTERVAL TIME

Use of high-quality and specially designed components

## QUICK CHANGE OF OIL TYPE

- e.g. PAG to POE oil
- Intelligent rinsing of the pipe system and service hoses

# COOL. COOLER. COOLUS.



# SPECS.



<b>DIMENSIONS</b>	572 x 545 x 1045 mm
<b>WEIGHT</b>	65 kg
<b>CASING</b>	Metal with robust plastic cover
<b>OPERATING POWER SUPPLY</b>	230 V / 50 Hz
<b>OPERATING TEMPERATURE RANGE</b>	+10 / +49°C
<b>REFRIGERANT</b>	R134a
<b>REFRIGERANT TANK</b>	11 kg
<b>REFRIGERANT SCALE</b>	60 kg loadable
<b>MAX. OPERATING PRESSURE</b>	20 bar
<b>COMPRESSOR</b>	1/3 HP
<b>RECOVERY RATE (LIQUID)</b>	300 g/min
<b>NON CONDENSABLE GAS DISCHARGE</b>	Automatic
<b>MAIN FILTER DRYER (1 PIECE)</b>	Type 660 Coaxial
<b>LARGE VENTILATOR FOR SAFE OPERATION</b>	D 172 mm
<b>MONITORING OF PRESSURE INCREASE IN THE A/C SYSTEM</b>	Automatic
<b>OLD OIL DISCHARGE</b>	Automatic
<b>OLD OIL BOTTLE CAPACITY - SEALED</b>	250 ml
<b>ÖL / UV ACCURACY</b>	± 2 g
<b>REFRIGERANT RECOVERY AND CHARGE ACCURACY</b>	± 15 g
<b>VACUUM PUMP CAPACITY</b>	100 l/min
<b>FINAL PRESSURE (MCLEOD ABS)</b>	0,05 mb
<b>ELECTRONIC PRESSURE SENSOR</b>	Integrated
<b>PAG / POE OIL CHARGE</b>	Automatic
<b>PAG / POE OIL BOTTLE CAPACITY</b>	250 ml
<b>UV ADDITIVE BOTTLE CAPACITY</b>	100 ml
<b>REFRIGERANT CHARGE</b>	Automatic
<b>FLUSHING PROGRAM</b>	Included
<b>REFRIGERANT MANAGEMENT SYSTEM</b>	Included
<b>CONVENIENT DISPLAY</b>	4 x 20 characters
<b>ACOUSTIC SIGNAL</b>	For errors and hints
<b>UPDATE OF THE VEHICLE DATA BASE</b>	Via USB port
<b>SET-UP OF OWN VEHICLE DATA BASE</b>	Included
<b>INTEGRATED PRINTER</b>	With multiple printing
<b>HIGH PRESSURE AND LOW PRESSURE VALVES</b>	Electronically controlled
<b>PRESSURE GAUGES (PULSE FREE) LP + HP</b>	CL 1.0 / D 80 mm
<b>PARKER QUICK COUPLERS</b>	SAE J639
<b>SERVICE HOSES 3.0 M</b>	SAE J2197
<b>EXTENSION KIT SERVICE HOSES</b>	Optional
<b>SERVICE HOSES COMPENSATION</b>	Automatic
<b>CERTIFICATIONS</b>	CE-certification by TÜV Süd



**GASHIRA MARSHALL**

Key Account Manager

M 021 280 2685

[gashira.marshall@wurth.co.nz](mailto:gashira.marshall@wurth.co.nz)

**Würth New Zealand Ltd.**

99 McLaughlins Road

Wiri

Auckland 2104

17 Syd Bradley Road

Dakota Park

Christchurch 8042

p: 0800 683 040

e: [sales@wurth.co.nz](mailto:sales@wurth.co.nz)

[www.wurth.co.nz](http://www.wurth.co.nz)



**CONTACT GASHIRA FOR PRICING AND  
TO ARRANGE A DEMONSTRATION**